


DVI To Fiber Converters + 1 audio, 1.25G, Uncompressed

Features

- Transmits DVI video signals up to 10km over a pair fiber optic cable;
- Support video resolution max up to 1080p@60Hz;
- Support towards independent audio transmission;
- Compliance with DVI 1.0 standard;
- High compatibility, can auto-match source and display device;
- Built-in automatic adjustment system, make the image smooth, clear and stable;
- Built-in ESD protection system;
- Simple to install, plug and play;





Application


- HD monitor transmission and power supply
- Security protection system, TV medical treatment
- Network telephone transmission, Intelligent house and home system
- Intelligent transportation supervisory system (ITS)
- High-speed Way supervisory/Tele-Communication System
- Long-distance Multi-media Schooling, Campus monitoring
- Long-distance broadcast television transmission system
- High-building Security Protection, Military Tele-Com project
- Smart City




> Specification

-		
Video		
Standards	DVI 1.0	
Maximum pixel clock	225MHz	
Maximum data rate	6.75Gbps	
Resolution range	1920*1080@60Hz	
Connector	DVI-D Interface	
DVI Cable Range	<5M (Resolution: 1920*1080@60Hz)	
Impedance	100Ω	
Audio		
Interface	3.5mm earphone seat	
Signal type	Stereo	
Optical fiber		
Interface	SFP model – LC connector	
Fiber type	Single-mode, single fiber	
Wavelength	Single-mode 1310nm	
Interface bandwidth	1.25Gbps	
Transmission distance	2Km	
Other		
Power supply	DC12V	
Power dissipation	MAX 6W	
LED indicator	S: Video signal connection indicator	
	P: System power indicator	
Temperature	Operating: -5°C ~ +70°C	
Humidity	Operating: 5% ~ 90%	
Dimension	94.5*73*26mm	
The warranty	1 year free warranty	


Connection



> Panel



Transmitter



Receiver

Ordering Information

Model NO.	Description
DVI0101-10G	DVI To Fiber Converters + 1-port RS232, 10G, Uncompressed
DVI0110-G	DVI To Fiber Converters + 1 audio, 1.25G, Uncompressed
DVI0111-3G	DVI To Fiber Converters + 1 audio+1-port RS232, 3G, Uncompressed

Packing List

- DVI optical fiber transmitter *1
- DVI optical fiber receiver * 1
- Fiber optic module * 2
- Power adapter * 2
- User manual * 1