



## 8-Port RS485/422 + 2-port 10/100BASE-T(X), Din-Rail, DC12-48V

### ➤ Features

- Support 2-port 10/100BASE-T(X) + 8-port RS-485/422;
- Support IEEE802.3/802.3u standard, store and forward Exchange Mode;
- Support TCP server, TCP client, UDP and Modbus TCP(RTU) serial transmission modes;
- Support 300~460800bps line speed non-blocking communication;
- Support TCP, IP, UDP, Modbus TCP, Modbus RTU, ARP, ICMP, HTTP and TFTP Client protocols;
- Support RTU Master mode, maximum support 16 TCP master connections in this mode;
- Support Web management;
- Support serial port settings, can connect two serial devices via Ethernet;
- Supports gateway, cross-routing communication;
- Low-power consumption design;
- Support 8 serial ports' isolation function, isolation voltage 500V AC;
- Metal housing with IP40 and high level EMC protection;
- Support wide voltage 12-48V DC power input;
- Support DIN-Rail Mounting or Wall Mounting installation;
- Working temperature range: -40~85°C;
- Warranty: 5 years



### ➤ Introduction

UPCOM MW1028 Din-Rail industrial serial server support 8-channel RS-485/422 + 2-port 10/100Base-T(X), adopts high-strength IP40 protective shell, industrial-grade EMC design, supports Auto-Negotiation adaptive technology, provides LED status indication, and supports voltage 12~48V DC power input to increase the reliability of the communication network.

MW1028 can easily and conveniently centralize the management of scattered serial devices and hosts through the network. The communication rate supports 300~460800bps optional. Built-in Modbus TCP and Modbus RTU protocol make it easy for users to connect Modbus Ethernet devices to Modbus serial devices. Based on industrial installation requirements, DIN35 rail or Wall Mounting installation mode provided. This product adopts the industry's excellent network solution, and the operating temperature range is -40~85°C, which can meet the requirements of various industrial serial communication solutions.

### ➤ Application Industries

- Industrial Automation
- Intelligent transportation supervisory system (ITS)
- High-speed Way supervisory/Tele-Communication System
- New Energy and Utilities
- Rail transportation industry

## ➤ Specification

Interface	
RJ45 port	10/100BASE-T(X) Auto-Negotiation speed,full/half duplex mode and MDI/MDI-X self-adaption
Serial port	RS-422 supports R-, R+, T-, T+ full-duplex modes,RS-485 supports A and B half-duplex working mode; RS-485/422 communication rate support 300~460800bps optional, isolated voltage 500V AC; Built-in Modbus TCP and Modbus RTU protocols, support RTU Master mode, maximum support 16 TCP master connections in this mode.
Ethernet Attribute	
10M forwarding speed	14881pps
100M forwarding speed	148810pps
Rate	10M/100Mbps
Transmission way	Store and forward
Interface connector	RJ45
Serial Port Attribute	
Standard	RS-485/422
RS-422 signal	T+, T-, R+, R-, GND
RS-485 signal	D+, D-, GND
Check bits	None, Even, ODD
Data bits	5bit, 6bit, 7bit, 8bit
Stop bits	1bit, 2bit
Baud rate	300~460800bps
Directional control	RS-485 adopts data flow auto control technology
Load capacity	RS-485/422 port supports 32 points polling environment ,can up to 128
Interface connector	RS-485/422 port adopts 6-bit 3.84mm spacing terminal
Interface protection	4000V surge protection
LED Indicator	
Power indicator	PWR
System running indicator	SYS
Serial port data status indicator	S1/S2/S3/S4/S5/S6/S7/S8
Power Supply	
Input	Wide voltage 12~48V DC power input,typical working voltage 12V/24V/48V,using 4-cores 7.62mm industrial power terminal
Idle running power	0.957W@24VDC
Full-load power	1.199W@24VDC.
Physical Characteristics	



## ➤ Ordering Information

Model NO.	Description
MW1011	1-channel RS232/RS-485/422 + 1-port 10/100Base-T(X) RJ45, DC12-48V, 500V Isolation
MW1012	2-channel RS-485+ 1-port 10/100Base-T(X) RJ45, DC12-48V, 500V Isolation
MW1024	4-channel RS-485/422 + 2-port 10/100Base-T(X) RJ45, DC12-48V, 500V Isolation
MW1028	8-channel RS-485/422+ 2-port 10/100Base-T(X) RJ45, DC12-48V, 500V Isolation

## ➤ Packing List

- Industrial Serial Device Server \*1
- User manual \* 1
- Certificate of quality \* 1
- Warranty card \* 1